

Revision: 30.11.2023

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.11.2023 Version number 2 (replaces version 1)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: <u>Unocol 38</u> · Article number: 102833

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category PC1 Adhesives, sealants

· Application of the substance / the mixture Adhesives

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

APM Technica AG
Max-Schmidheiny-Str.201
CH-9435 HEERBRUGG
SCHWEIZ

· Further information obtainable from:

Tel. +41 71 788 31 00 (At office times only)

E-Mail: msds@apm-technica.com

1.4 Emergency telephone number:

Tox Info Suisse Freiestrasse 16 CH-8032 Zürich

Swiss Emergency phone number: 145 (24h). From outside of Switzerland: +41 44 251 51 51

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07 GHS09

· Signal word Warning

(Contd. on page 2)

Printing date 30.11.2023 Version number 2 (replaces version 1) Revision: 30.11.2023

Trade name: Unocol 38

(Contd. of page 1)

· Hazard-determining components of labelling:

2-hydroxyethyl methacrylate

Isobornylmethacrylate

methacrylic acid, monoester with propane-1,2-diol

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms





GHS07 GHS09

· Signal word Warning

· Hazard-determining components of labelling:

2-hydroxyethyl methacrylate

Isobornylmethacrylate

methacrylic acid, monoester with propane-1,2-diol

Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves / eye protection / face protection.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

| CAS: 868-77-9 | 2-hydroxyethyl methacrylate | >10–≤50% |
|-------------------|---|----------|
| EINECS: 212-782-2 | ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 | |
| CAS: 7534-94-3 | Isobornylmethacrylate Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | ≥20–<25% |
| | tert-butyl perbenzoate Org. Perox. C, H242; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | ≥0–<10% |

Printing date 30.11.2023 Version number 2 (replaces version 1) Revision: 30.11.2023

Trade name: Unocol 38

| | | (Contd. of page 2) |
|-------------------|--|--------------------|
| CAS: 27813-02-1 | methacrylic acid, monoester with propane-1,2-diol | ≥1–<10% |
| EINECS: 248-666-3 | Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 | |
| CAS: 79-10-7 | acrylic acid | ≥2.5–<5% |
| | Flam. Liq. 3, H226; Skin Corr. 1A, H314; Aquatic Acute 1, H400; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 Specific concentration limit: STOT SE 3; H335: C ≥ 1 % | |
| CAS: 24650-42-8 | 2,2-dimethoxy-1,2-diphenylethan-1-one | ≥0.25-<2.5% |
| EINECS: 246-386-6 | Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | |
| CAS: 79-41-4 | methacrylic acid | ≥0–<1% |
| EINECS: 201-204-4 | Skin Corr. 1A, H314; | |
| | Specific concentration limit: STOT SE 3; H335: C ≥ 1 % | |

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

Printing date 30.11.2023 Version number 2 (replaces version 1) Revision: 30.11.2023

Trade name: Unocol 38

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: Protect from heat.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

79-10-7 acrylic acid

OEL Short-term value: 59* mg/m³, 20* ppm Long-term value: 29 mg/m³, 10 ppm IOELV, *1-minute reference period

79-41-4 methacrylic acid

OEL Short-term value: 140 mg/m³, 40 ppm Long-term value: 70 mg/m³, 20 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Printing date 30.11.2023 Version number 2 (replaces version 1) Revision: 30.11.2023

Trade name: Unocol 38

· Material of gloves

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical stateColour:Odour:FluidGreenCharacteristic

• Odour threshold: Not determined. • Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range Undetermined. Flammability Not applicable.

Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: >97 °C

Decomposition temperature: Not determined. pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.
• Vapour pressure at 20 °C: <4.5 hPa

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid · Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product does not present an explosion hazard.

Heating may cause an explosion.

· Solvent content:

· **VOC (EC)** <3.00 %

(Contd. on page 6)

Version number 2 (replaces version 1) Printing date 30.11.2023 Revision: 30.11.2023

Trade name: Unocol 38

| | | (Contd. of pag |
|--|-----------------|----------------|
| Change in condition | | |
| Evaporation rate | Not determined. | |
| Information with regard to physical hazard | | |
| classes | | |
| Explosives | Void | |
| Flammable gases | Void | |
| Aerosols | Void | |
| Oxidising gases | Void | |
| Gases under pressure | Void | |
| Flammable liquids | Void | |
| Flammable solids | Void | |
| Self-reactive substances and mixtures | Void | |
| Pyrophoric liquids | Void | |
| Pyrophoric solids | Void | |
| Self-heating substances and mixtures | Void | |
| Substances and mixtures, which emit | | |
| flammable gases in contact with water | Void | |
| Oxidising liquids | Void | |
| Oxidising solids | Void | |
| Organic peroxides | Void | |
| Corrosive to metals | Void | |
| Desensitised explosives | Void | |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Keep away from UV and sunlight. Temperatures above 65°C may cause exothermic nonhazardous polymerisation.

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

| LD/LC50 | values rel | evant for classification: |
|------------|------------------------|------------------------------|
| ATE (Acu | te Toxicity | y Estimates) |
| Oral | LD50 | >5,903–20,048 mg/kg (rat) |
| Dermal | LD50 | >9,333–28,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | >367–1,100 mg/l |
| 868-77-9 | 2-hydroxy | ethyl methacrylate |
| Oral | LD50 | 5,050 mg/kg (rat) |
| 614-45-9 1 | ert-butyl _l | perbenzoate |
| Oral | LD50 | 1,012 mg/kg (rat) |
| 79-10-7 ad | crylic acid | |
| Oral | LD50 | 250 mg/kg (rat) |
| | | (Contd. on page |

Printing date 30.11.2023 Version number 2 (replaces version 1) Revision: 30.11.2023

Trade name: Unocol 38

| | | | (Contd. of page 6) |
|-----------|--------------------------|---------------------|--------------------|
| Dermal | LD50 | 280 mg/kg (rabbit) | |
| 79-41-4 ı | 79-41-4 methacrylic acid | | |
| Oral | LD50 | 1,332 mg/kg (mouse) | |
| Dermal | LD50 | 500 mg/kg (rabbit) | |

- Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| · European waste catalogue | | |
|--|---|--|
| 08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances | | |
| HP4 Irritant - skin irritation and eye damage | | |
| HP5 | HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity | |
| HP13 Sensitising | | |
| HP14 | Ecotoxic | |

(Contd. on page 8)

Printing date 30.11.2023 Version number 2 (replaces version 1) Revision: 30.11.2023

Trade name: Unocol 38

(Contd. of page 7)

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

| SECTION 14: Transport information | |
|--|---|
| · 14.1 UN number or ID number · ADR, IMDG, IATA | UN3082 |
| · 14.2 UN proper shipping name · ADR | 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ACRYLIC ACID, STABILIZED, Isobornylmethacrylate) |
| · IMDG | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ACRYLIC ACID, STABILIZED, Isobornylmethacrylate), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ACRYLIC ACID, STABILIZED, Isobornylmethacrylate) |
| · 14.3 Transport hazard class(es) | |
| ADR, IMDG, IATA | |
| · Class | 9 Miscellaneous dangerous substances and articles. |
| · 14.4 Packing group · ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): · Special marking (IATA): | Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree) |
| · 14.6 Special precautions for user | Warning: Miscellaneous dangerous substances and articles. |
| Hazard identification number (Kemler code): EMS Number: Segregation groups Stowage Category | 90 F-A,S-F (SGG1) Acids A |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · Transport/Additional information: | |
| · ADR · Limited quantities (LQ) · Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · Transport category · Tunnel restriction code | 3 (-) |

(Contd. on page 9)

Printing date 30.11.2023 Version number 2 (replaces version 1) Revision: 30.11.2023

Trade name: Unocol 38

| | (Contd. of page 8) |
|------------------------------|--|
| IMDG Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| UN "Model Regulation": | UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ACRYLIC ACID, STABILIZED, ISOBORNYLMETHACRYLATE), 9, III |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H226 Flammable liquid and vapour.

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 10)

Version number 2 (replaces version 1) Revision: 30.11.2023 Printing date 30.11.2023

Trade name: Unocol 38

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation

Serious eve damage/irritation

Skin sensitisation

Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-

term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. of page 9)

· Department issuing SDS: Technology · Contact: msds@apm-technica.com · Date of previous version: 30.11.2023 · Version number of previous version: 1

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 3: Flammable liquids - Category 3

Org. Perox. C: Organic peroxides - Type C/D

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.