

Revision: 29.09.2023

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.09.2023 Version number 3 (replaces version 2)

SECTION 1: Identification of the substance/mixture and of the company/

undertaking

· 1.1 Product identifier

· Trade name: Epicol 284281 Part B

· Article number: 284281B

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category PC1 Adhesives, sealants

Application of the substance / the mixture Adhesives

1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

APM Technica AG Max-Schmidheiny-Str.201 CH-9435 HEERBRUGG SCHWEIZ

· Further information obtainable from:

Tel. +41 71 788 31 00 (At office times only)

E-Mail: msds@apm-technica.com

1.4 Emergency telephone number:

Tox Info Suisse Freiestrasse 16 CH-8032 Zürich

Swiss Emergency phone number: 145 (24h). From outside of Switzerland: +41 44 251 51 51

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Skin Irrit. 2

H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 29.09.2023 Version number 3 (replaces version 2) Revision: 29.09.2023

Trade name: Epicol 284281 Part B

· Hazard pictograms

(Contd. of page 1)







GHS05 GHS07 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms







GHS05 GHS07 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)

· Hazard statements

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 29.09.2023 Version number 3 (replaces version 2) Revision: 29.09.2023

Trade name: Epicol 284281 Part B

		(Contd. of page 2
Dangerous componen	ts:	
CAS: 68911-25-1 EC number: 701-270-9		>25–≤100%
	♦ Eye Dam. 1, H318; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 1332-58-7	Kaolin substance with a Community workplace exposure limit	>25–≤100%
CAS: 1333-86-4 EINECS: 215-609-9	Carbon black Self-heat. 2, H252	≤2.5%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	<1%

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 29.09.2023 Version number 3 (replaces version 2) Revision: 29.09.2023

Trade name: Epicol 284281 Part B

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

1332-58-7 Kaolin

OEL Long-term value: 2 mg/m³

1333-86-4 Carbon black

OEL Long-term value: 3* mg/m3

*inhalable fraction

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Version number 3 (replaces version 2) Revision: 29.09.2023 Printing date 29.09.2023

Trade name: Epicol 284281 Part B

· Penetration time of glove material

(Contd. of page 4)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Dark grey · Odour: Characteristic · Odour threshold: Not determined. • Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range >152 °C · Flammability Not applicable.

Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined.

>94 °C · Flash point:

· Decomposition temperature: Not determined. · pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic at 20 °C: 40,000-80,000 mPas

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined. Vapour pressure: Not determined.

Density and/or relative density

· Density at 20 °C: 1.24-1.32 g/cm³ · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health

and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· VOC (EC) 0.00 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

· Explosives Void

(Contd. on page 6)

Printing date 29.09.2023 Version number 3 (replaces version 2) Revision: 29.09.2023

Trade name: Epicol 284281 Part B

		(Contd. of page
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values rel	evant for classification:		
1333-86-4	Carbon b	lack		
Oral	LD50	10,000 mg/kg (rat)		
13463-67-	13463-67-7 titanium dioxide			
Oral	LD50	>20,000 mg/kg (rat)		
Dermal	LD50	>10,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	>6.82 mg/l (rat)		

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 29.09.2023 Version number 3 (replaces version 2) Revision: 29.09.2023

Trade name: Epicol 284281 Part B

· 11.2 Information on other hazards

(Contd. of page 6)

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	
HP4	Irritant - skin irritation and eye damage	
HP13	Sensitising	
HP14	Ecotoxic	

- Uncleaned packaging:
- · **Recommendation:** Disposal must be made according to official regulations.

ARDOUS atty acids, C18- th 3,3'-
ne)) DUS atty acids, C18-
i

Printing date 29.09.2023 Version number 3 (replaces version 2) Revision: 29.09.2023

Trade name: Epicol 284281 Part B

(Contd. of page 7) unsaturated, dimers, polymers with 3,3'oxybis(ethyleneoxy)bis(propylamine)), MARINE POLLUTANT **ENVIRONMENTALLY HAZARDOUS** ·IATA SUBSTANCE, LIQUID, N.O.S. (Fatty acids, C18unsaturated, dimers, polymers with 3,3'oxybis(ethyleneoxy)bis(propylamine)) · 14.3 Transport hazard class(es) · ADR. IMDG. IATA · Class 9 Miscellaneous dangerous substances and articles. · Label 9 · 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: · Marine pollutant: Symbol (fish and tree) Symbol (fish and tree) · Special marking (ADR): Special marking (IATA): Symbol (fish and tree) · 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. · Hazard identification number (Kemler code): 90 · EMS Number: F-A,S-F · Stowage Category · 14.7 Maritime transport in bulk according to **IMO** instruments Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · Transport category 3 Tunnel restriction code (-)· Limited quantities (LQ) 5L Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 **UN "Model Regulation": UN 3082 ENVIRONMENTALLY HAZARDOUS** SUBSTANCE, LIQUID, N.O.S. (FATTY ACIDS, C18-UNSATURATED, DIMERS, POLYMERS WITH 3,3'-OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE)), 9, III

Printing date 29.09.2023 Version number 3 (replaces version 2) Revision: 29.09.2023

Trade name: Epicol 284281 Part B

(Contd. of page 8)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E1 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H252 Self-heating in large quantities; may catch fire.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation
Serious eye damage/irritation
Skin sensitisation
Hazardous to the aquatic environment - shortterm (acute) aquatic hazard
Hazardous to the aquatic environment - long-

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- · Department issuing SDS: Technology
- · Contact: msds@apm-technica.com

term (chronic) aquatic hazard

- · Date of previous version: 29.09.2023
- \cdot Version number of previous version: 2

(Contd. on page 10)

Printing date 29.09.2023 Version number 3 (replaces version 2) Revision: 29.09.2023

Trade name: Epicol 284281 Part B

Abbreviations and acronyms:

(Contd. of page 9)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Self-heat. 2: Self-heating substances and mixtures - Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.